



NEWS RELEASE

German Precision Optics Launches New SPECTRA™ 6X Riflescopes

RICHMOND, Va. (March 2, 2021) — German Precision Optics (GPO) announces six new riflescopes to its line of premium optics. Designed for today's discriminating hunter, the new SPECTRA™ 6X riflescope lineup offers precise, reliable and top-of-the-line performance to meet the demands of any situation hunters may find themselves in. A 30mm main tube, proprietary GPObright™ high-transmission lens coating technology, iControl™ illumination technology, PASSIONdrop™ hydrophobic exterior lens coatings and a double HD glass objective lens are just some of the features you will find in these models. Models in the 6X line include the SPECTRA™ 1-6x24i, 1,5-9x32i, 1,5-9x44i, 2-12x44i, 2-12x50i, and 3-18x56i.

Both the SPECTRA 1-6x24i and 1,5-9x32i riflescopes are compact and lightweight, with magnification from 1x to 9x between to 2 models, which allows for quick shooting on fast-moving targets at close range, and a choice between 24mm and 32mm objective lens diameter. The GPO G4i reticle enhances the ability to make fast and accurate shot placements. The SPECTRA 1,5-9x44i also offers a wide magnification range for a scope of its size, but has a 44mm objective lens for enhanced light gathering, and the GPO G4i Drop reticle for precise long-range shot placements.

For medium- and long-range hunting, both the SPECTRA™ 2-12x44i and 2-12x50i feature magnification from 2x to 12x and either the BRWi ballistic reticle or the G4i, with your choice of either a 44mm or 50mm objective lens for enhanced light transmission. For the ultimate in light transmission and low-light accuracy, the SPECTRA 3-18x56i features magnification from 3x to 18x, a massive 56mm objective lens, and the exclusive GPO BRi reticle, which gives you a fully illuminated ballistic reticle with illuminated holdover markers, for the ultimate in long-range precision in low light.

Exclusive to GPO, the proprietary iCONTROL™ illumination system can be adjusted between barely visible for low-light conditions or extremely bright for daylight usage. The system automatically powers down the illumination when the electronic module has been stationary for more than three hours and alerts the user when the battery has 15 percent power remaining.

With the introduction of the Spectra riflescope lines, GPO has modernized the hunting turret systems for the shooting enthusiast who wants both a ballistic turret for easy dialing but also protection from the elements of outdoor field use with a capped ballistic turret. With a low-profile knob that has easy-to-read dial numbers, the aluminum cap fits snugly over the top.

This system has clockwise rotating cm click turrets with solid knurled knobs easy to grab in any hunting environment. A blank turret is provided in every box for customization.

The new SPECTRA 6x line of riflescopes are crafted from a solid, one-piece dust-proof, waterproof, nitrogen-filled body that offers constant point-of-impact and the ultimate in strength and durability. All SPECTRA™ 6X riflescopes come with an instruction manual, cleaning cloth, bikini scope cover, CR2032 battery, and throw lever. All GPO products purchased in the USA include the GPO, USA's Spectacular Lifetime Warranty™. Full details on this industry-changing warranty can be found at www.gpo-usa.com. Currently available at retailers nationwide and at www.gpo-usa.com, MSRPs are: 1-6x24i, \$799.99; 1.5-9x32i \$899.99; 1.5-9x44i \$899.99; 2-12x44i \$899.99; 2-12x50i \$949.99; 3-18x56i, \$1099.99

About GPO USA

German Precision Optics was founded on the premise that design, engineering and quality management is 100 percent controlled in Germany to its strictest standards, yet products can be produced at some of the largest production facilities around the world. This unique corporate structure allows GPO to offer the highest quality products with better features at a significantly better price. The company is 100-percent confident that all of its products will not only function perfectly but will exceed all expectations. Therefore, GPO, USA has created an industry-leading Spectacular Lifetime Warranty™. With outstanding professional service, GPO USA will take care of its products before, during, and after the purchase at no charge—EVER. Founded in 2016, GPO has its US headquarters in Richmond, VA. For more information on GPO US visit www.gpo-usa.com or call 844-MY BINOS (844-692-4667.)

Editorial Contact:

Karen Lutto


210-451-9113 (office)

804-539-6699 (cell)


karen@hunteroc.com

HOC Website: www.hunteroc.com


Spectra 1.6-24i




Spectra 1.5-9x32i




Spectra 1.5-9x44i




Spectra 2-12x44i



Spectra 2-12x50i



Spectra 3-18x56i



GPO RIFLESCOPE TECHNICAL SPECIFICATIONS

SPECTRA 6X SPECTRA 6X SPECTRA 6X SPECTRA 6X SPECTRA 6X SPECTRA 6X

Optical parameter	Description	Value	1-6x24i		1.5-9x32i		1.5-9x44i		2-12x44i		2-12x50i		3-18x56i	
			Min	Max										
Item #			RS610		RS620		RS630		RS640		RS650		RS660	
Magnification			1x	6x	1.5x	9x	1.5x	9x	2x	12x	2x	12x	3x	18x
Field of View (FOV)	Size of overall image	ft/100y	128	22	86	14	86	14	65	11	64	11	34	6
Field of View (FOV)	Size of overall image	m/100m	42	7	28	4.6	28	4.6	21	3.5	21	3.5	11.1	1.9
Objective diameter	Effective diameter	mm	24		32		44		44		50		56	
Exit pupil diameter	Measurement of the pupillary ocular beam	mm	9.5	4	9.5	3.5	9.5	4.9	9.5	3.6	9.5	4.2	9.5	3.1
Eye Relief	From the last optical surface	inches	4		4		4		4		4		3.74	
Eye Relief	From the last optical surface	mm	97		97		97		97		97		95	
Focal plane	F2 - non-magnifying reticle F1 - magnifying reticle		F2		F2		F2		F2		F2		F2	
Travel value per click	1 Click = x / 100y	inches	.36"		.36"		.36"		.36"		.36"		.36"	
Travel value per click	1 Click = x / 100m	cm	1		1		1		1		1		1	
Turret rotation for elevation	CCW - Counterclockwise up CW - Clockwise up	direction	CW											
Elevation range total	100y	inches	144		144		144		144		144		90	
Elevation range total	100m	cm	400		400		400		400		400		250	
Windage range total	100y	inches	144		144		144		144		144		90	
Windage range total	100m	cm	400		400		400		400		400		250	
Parallax compensation	Parallax free at x distance		100m		100m		100m		100m		100m		10y to infinity	
Transmission Daylight	ISO 14490-5:2005		90.00%		90.00%		90.00%		90.00%		90.00%		90.00%	
Height	Without covers	inches	1.88		1.88		1.88		1.88		1.88		2.1	
Height	Without covers	mm	47.9		47.9		47.9		47.9		47.9		54	
Width	Without covers	inches	2.66		2.66		2.66		2.66		2.66		3.34	
Width	Without covers	mm	67.5		67.5		67.5		67.5		67.5		85	
Weight	Without covers	ounces	16.9		19.5		20.28		20.28		20.92		29.27	
Weight	Without covers	grams	459		496		575		575		593		830	
Turrets	Type		Capped Passion Trac New Turret		Capped Passion Trac New Turret		Capped Passion Trac New Turret		Capped Passion Trac New Turret		Capped Passion Trac New Turret		Capped Passion Trac New Turret	
Reticle Options	G4i = German #4 illuminated G4i Drop = G4i and ballistic drop BR = Ballistic reticle BRi = Illuminated ballistic reticle BRWi = Illuminated ballistic/wind reticle		G4i		G4i		G4i Drop		BRWi		G4i		BRi	
Suggest Selling Price			\$799.99		\$899.99		\$899.99		\$899.99		\$949.99		\$1,099.99	