



**NEWS RELEASE
FOR IMMEDIATE RELEASE**



**German Precision Optics RANGETRACKER™ 1800 Rangefinder
Now Available In Black at a Lower Price**

RICHMOND, Va. (Feb. 23, 2021) — In response to customer requests, German Precision Optics (GPO) USA's popular compact, lightweight, one-handed RANGETRACKER 1800 Rangefinder is now available in black. Introduced last year in green, this handheld rangefinder allows the hunter to accurately range its target out to 1800 yards with one of the fastest laser rangefinding systems on the market.

The GPO RANGETRACKER™ features state-of-the-art optical and electronic technology for both long-range rifle hunting and close archery usage (6 yards.) Designed with a high transmission optical system coated with GPO's proprietary GPObright™ lens coatings, both line of sight and/or True-range™ adjusted angle distance readings, a Hyperscan™ feature that provides three readings per second, and Targetseeker™ technology that offers "best" and "last" laser hits. The display is an HLDC system that allows up to 25 percent more light to get through the optical system, making it usable in very low-light situations.

"We do our best to answer the needs of our customers," said Mike Jensen, GPO owner and CEO. "They requested this product in black. We not only are bringing it out in black, but we have also lowered the price."

The RANGETRACKER now available in both green and black has a new suggested retail selling price of \$349.99 and is currently available at retailers nationwide. For more

information on this product line [CLICK HERE](#), call 1-844-MY-BINOS (692-4667) or visit www.gpo-usa.com.

About GPO USA

German Precision Optics was founded on the premise that design, engineering and quality management is 100-percent controlled in Germany to its strictest standards, yet products can be produced at some of the largest production facilities around the world. This unique corporate structure allows GPO to offer the highest quality products with better features at a significantly better price. The company is 100-percent confident that all of its products will not only function perfectly but will exceed all expectations. Therefore, GPO, USA has created an industry-leading Spectacular Lifetime Warranty™. With outstanding professional service, GPO USA will take care of its products before, during, and after the purchase at no charge, ever. Founded in 2016, GPO has its U.S. headquarters in Richmond, Va. For more information on GPO USA, visit www.gpo-usa.com or call 844-MY BINOS (844-692-4667).

Editorial Contact:

Karen Lutto

210-451-9113 (office)

804-539-6699 (cell)

karen@hunteroc.com

HOC Website: www.hunteroc.com

GPO RANGETRACKER 1800 TECHNICAL SPECIFICATIONS
GPO RANGETRACKER 1800 TECHNICAL SPECIFICATIONS

Optical parameter	Description	6X20	Optical parameter	Description	6X20
Magnification		6X	Range Maximum	Reflective/Solid Targets (m)	1645
Field of View (angle)		7.5 degr.	Range Maximum	Reflective/Solid Targets (y)	1800
Field of View (FOV)	Meters at 1000 meters	132	Range Maximum	Tree (m)	640
Field of View (FOV)	Feet at 1000 yards	400	Range Maximum	Tree (y)	700
Objective diameter	Effective diameter (mm)	20	Range Maximum	Deer (m)	640
Ocular diameter	Edge diameter (mm)	25	Range Maximum	Deer (y)	700
Exit pupil diameter	Measurement of the pupillary ocular beam	3.3	Minimum Range	Meters	5.5
Eye Relief	From the last optical surface	16mm	Minimum Range	Yards	6
Eye Relief	From the last optical surface	0.63	Laser Response Time	Seconds	0.33
Housing	Main body and hinge	Polycarbonate	GPO RANGETRACKER 1800 FEATURES		
Diopter Adjustment range		3	True Angle	Adjusted shooting distance	yes
Waterproof	Mbars	IPX4	Angle	Shows the angle degree	yes
Prism trpe		Roof	LOS Mode	Line of sight only	yes
Transmission Daylight	ISO 14490-5:2005	90%	Scan Mode	3 readings per second	yes
Height	Without covers (mm)	76mm	Dual Target Seeker	Best and Last laser hit	yes
Height	Without covers (in)	3	Temperature	Farenheight / celcius	yes
Width	Fully extended (mm)	33mm	Display	OLED	no
Width	Fully extended (in)	1.3	Display Color	Black	yes
Length	At outside diameter (mm)	94mm	Battery Type	CR2	yes
Length	At outside diameter (in)	3.7	Angle Sensor	Max / Min degree	+/- 60 degrees
Weight	Without covers (grams)	148g	ITEM #	RT1800B	
Weight	Without covers (ounces)	5.2	UPC #	852885007540	

###